




# Řetězová kola s nábojem 5/8" x 3/8" (10B -1 -2 -3) pro Taper Lock® pro válečkové řetězy DIN 8187/ ISO R606

Materiál


viz. níže




Provedení 1




Provedení 2




Provedení 3



Provedení 4



Provedení 5



Provedení 6

## 1-řadé

| Obj. číslo | Počet zubů<br>z | de    | dp     | Pouzdro<br>Taper Lock® | Provedení | dm  | A  |
|------------|-----------------|-------|--------|------------------------|-----------|-----|----|
| T 43993    | 13              | 73.2  | 66.33  | 1008                   | 1         | 47  | 22 |
| T 43994    | 15              | 83.2  | 76.35  | 1210                   | 1         | 60  | 25 |
| T 64995    | 16              | 88.3  | 81.37  | 1210                   | 1         | 63  | 25 |
| T 43995    | 17              | 93.3  | 86.39  | 1610                   | 1         | 71  | 25 |
| T 64996    | 18              | 98.3  | 91.42  | 1610                   | 1         | 71  | 25 |
| T 43996    | 19              | 103.3 | 96.44  | 1610                   | 1         | 75  | 25 |
| T 64997    | 20              | 108.4 | 101.49 | 1610                   | 1         | 76  | 25 |
| T 43997    | 21              | 113.4 | 106.51 | 1610                   | 1         | 76  | 25 |
| T 64998    | 22              | 118.4 | 111.55 | 1610                   | 1         | 76  | 25 |
| T 43998    | 23              | 123.5 | 116.58 | 1610                   | 1         | 76  | 25 |
| T 64999    | 24              | 128.5 | 121.62 | 2012                   | 1         | 90  | 32 |
| T 43999    | 25              | 133.6 | 126.66 | 2012                   | 1         | 90  | 32 |
| T 44000    | 27              | 143.6 | 136.74 | 2012                   | 1         | 90  | 32 |
| T 44001    | 30              | 158.8 | 151.87 | 2012                   | 1         | 90  | 32 |
| T 44002    | 38              | 199.1 | 192.23 | 2012                   | 1         | 100 | 32 |
| T 44004    | 57              | 296.6 | 288.18 | 2012                   | 6         | 111 | 32 |
| T 44005    | 76              | 392.5 | 384.16 | 2012                   | 6         | 111 | 32 |

## 2-řadé

|         |    |       |        |      |   |    |      |
|---------|----|-------|--------|------|---|----|------|
| T 44067 | 15 | 83.2  | 76.35  | 1210 | 3 | -  | 25.5 |
| T 44068 | 17 | 93.3  | 86.39  | 1610 | 3 | -  | 25.5 |
| T 44069 | 19 | 103.3 | 96.44  | 1610 | 3 | -  | 25.5 |
| T 44070 | 21 | 113.4 | 106.51 | 1610 | 3 | -  | 25.5 |
| T 44071 | 23 | 123.5 | 116.58 | 1610 | 3 | -  | 25.5 |
| T 44072 | 25 | 133.6 | 126.66 | 2012 | 2 | 90 | 32.0 |
| T 44073 | 27 | 143.6 | 136.74 | 2012 | 2 | 90 | 32.0 |
| T 44074 | 30 | 158.8 | 151.87 | 2012 | 2 | 90 | 32.0 |

## 3-řadé

|         |    |       |        |      |   |     |      |
|---------|----|-------|--------|------|---|-----|------|
| T 65029 | 15 | 83.2  | 76.35  | 1215 | 5 | -   | 42.1 |
| T 65030 | 17 | 93.3  | 86.39  | 1215 | 5 | -   | 42.1 |
| T 65031 | 19 | 103.3 | 96.44  | 1615 | 5 | -   | 42.1 |
| T 65032 | 21 | 113.4 | 106.51 | 1615 | 5 | -   | 42.1 |
| T 65033 | 23 | 123.5 | 116.58 | 2012 | 5 | -   | 42.1 |
| T 65034 | 25 | 133.6 | 126.66 | 2517 | 4 | 105 | 44.0 |
| T 65035 | 27 | 143.6 | 136.74 | 2517 | 4 | 110 | 44.0 |
| T 65036 | 30 | 158.8 | 151.87 | 2517 | 4 | 120 | 44.0 |

| B1  | B2   | B3   | r3 | c   | b1 |
|-----|------|------|----|-----|----|
| 9.1 | 25.5 | 42.1 | 16 | 1.6 | 9  |

### Materiál:

Provedení 1 - 5: Ocel C 43  
Provedení 6: Šedá litina

### Poznámka:

Upínací pouzdra Taper Lock® viz. strana K 25 - K 29.

Rozměry uvedeny v mm.