

LOCTITE®

55 PIPE SEALING CORD



- Allows fittings to be “backed-off” for alignment without fear of leakage
- Suitable for hot and cold water, potable water, gas, compressed air and industrial oils

ADJUSTABLE

FASTER

SAFER

EASIER

Henkel Technologies

LOCTITE®

A better joint for pipe systems

Loctite® 55 Pipe Sealing Cord is a new, faster, cleaner, more versatile pipe sealant which out-dates traditional tapes and hemp/paste combinations. It therefore enables the improvements required of today's pipe systems. Naturally, it complies with all latest regulations.

4 easy steps....



....to a better joint

- **Loctite® 55**
replaces tapes, hemp and pastes
- **Loctite® 55**
seals pipe threads up to 4"
- **Loctite® 55**
has UK and European approvals for potable water and gas
- **Loctite® 55**
seals against hot or cold water, gas, compressed air, industrial and heating oils

- **Loctite® 55**
allows fittings to be "backed-off" for alignment without fear of leakage
- **Loctite® 55**
gives the bonus of speed, cleanliness and an assured first time seal that will not require return visits
- **Loctite® 55**
can be safely used on cast iron, steel, brass, copper, chrome, nickel-plated and galvanised surfaces, stainless steel and plastic parts

A single reel of Loctite 55 will seal:

Thread size	1/2"	3/4"	1"
Approx. number of joints - 150 metre pack	385	260	180
Approx. number of joints - 50 metre pack	130	85	60



- **Loctite® 55**
is easily applied directly from these handy, pocket-sized, protective containers with a built-in cutter



Available in 150 and 50 metre packs

Henkel Loctite Adhesives Limited

Technologies House, Wood Lane End
Hemel Hempstead, Hertfordshire HP2 4RQ
Tel: 01442 418305 Fax: 01442 418228
E-mail: loctite@henkel.co.uk
Website: www.loctite.co.uk

Available from:

